CHATSWORTH PRODUCTS, INC.

Optimize.
Store.
Secure.

Cable Management

Double-Sided Version Shown

Evolution® Cable Management

Applications:
Network facilities and data center computer rooms

Key Features:
- Closed, single or double-sided and combination vertical cable management
- T-shaped cable fingers with rounded edges organize cables
- Cable openings align with each rack-mount unit on the rack and pass 48 patch cords
- Double-sided versions have Movable Mid-Sections allowing a 40/60, 50/50 or 60/40 front/rear split of the interior storage space
- Includes a removable, hinged door with a two-point latch and single door knob
- Front door style matches the TeraFrame® Family of Cabinets

Width (5):
- 6″ (150 mm)
- 8″ (200 mm)
- 10″ (250 mm)
- 12″ (300 mm)
- 15″ (380 mm)

Height (3):
- 6′0″ (1.8 m)
- 7′0″ (2.1 m)
- 8′0″ (2.4 mm)

Depth (3):
- 13.2″ (335 mm)
- 24.5 (622 mm)*
- 20.2″ (513 mm)*

**Double-sided versions*

Construction:
- Riveted and welded, steel and plastic

Single-Sided Version Shown

Velocity™ Cable Management

Applications:
Network facilities

Key Features:
- Closed, single or double-sided vertical cable management
- T-shaped cable fingers with rounded edges organize cables
- Cable openings align with each rack-mount unit on the rack and pass 24 patch cords
- Includes removable, hinged snap-on covers
- Ships unassembled in compact packaging for easy shipping, handling and storage
- Tool-less snap-together design for quick and easy assembly

Width (4):
- 3.6″ (92 mm)
- 6″ (150 mm)
- 10″ (250 mm)
- 12″ (300 mm)

Height (3):
- 70″ (1778 mm) for 6′H (1.8 m) racks
- 80.5 (2045 mm) for 7′H (2.1 m) racks
- 91″ (2311 mm) for 8′H (2.4 m) racks

Depth (2):
- 9.5″ (241 mm)
- 16″ (406 mm)*

**Double-sided version*

Construction:
- Snap-together, steel and plastic

Double-Sided Version Shown

MCS Master Cabling Section

Applications:
Network facilities and data center computer rooms

Key Features:
- Closed, single or double-sided vertical cable management
- T-shaped cable fingers with rounded edges organize cables
- Cable openings align with each rack-mount unit on the rack and pass 24 patch cords
- Includes removable, hinged latch-closure door(s)
- Available with standard (MCS) and deeper extended fingers (MCS-EFX)

Width (4):
- 4.4″ (112 mm)
- 6″ (150 mm)*
- 10″ (250 mm)*
- 12″ (300 mm)*

Height (7):
- 5′6″ (1.7 m)
- 6′0″ (1.8 m)
- 6′6″ (2.0 m)
- 7′0″ (2.1 m)*
- 7′6″ (2.3 m)*
- 8′0″ (2.4 m)*
- 9′0″ (2.7 m)

Depth (4):
- 8.08″ (205.2 mm)
- 10.62″ (269.7 mm)*
- 16.15″ (410.2 mm)
- 21.23″ (539.2 mm)*

**MCS-EFX versions*

Construction:
- Riveted and bolted, aluminum and plastic

Double-Sided Version Shown

VCS Vertical Cabling Section

Applications:
Network facilities

Key Features:
- Open, single or double-sided vertical cable management
- Large side openings are edge protected
- Spin-latch closures secure cables
- Covers and snap-on T-Shaped Finger Snaps Cable Guides are available as accessories

Width (2):
- 3.65″ (92.7 mm)
- 6″ (150 mm)

Height (7):
- 5′6″ (1.7 m)
- 6′0″ (1.8 m)
- 6′6″ (2.0 m)
- 7′0″ (2.1 m)*
- 7′6″ (2.3 m)
- 8′0″ (2.4 m)*
- 9′0″ (2.7 m)*

Depth (2):
- 6.38″ (162.1 mm)
- 12.75″ (323.9 mm)*

** Double-sided versions*

Construction:
- Riveted and bolted, aluminum and plastic

CCS Combination Cabling Section

Applications:
Network facilities

Key Features:
- Combination, double-sided vertical cable management
- MCS-style front side and VCS-style back side
- Front side includes a removable, hinged latch-closure door
- T-shaped cable fingers with rounded edges organize cables
- Cable openings align with each rack-mount unit on the rack and pass 24 patch cords
- Back side has edge protected openings and spin-latch closures
- Available with standard (CCS) and deeper extended fingers (CCS-EFX)

Width (4):
- 3.65″ (92.7 mm)
- 6″ (150 mm)*
- 10″ (250 mm)*
- 12″ (300 mm)*

Height (5):
- 6′0″ (1.8 m)
- 7′0″ (2.1 m)*
- 7′6″ (2.3 m)*
- 8′0″ (2.4 m)*
- 9′0″ (2.7 m)

Depth (3):
- 12.24″ (310.9 mm)
- 14.61″ (371.1 mm)
- 14.94″ (379.5 mm)*

**CCS-EFX versions*

Construction:
- Riveted and bolted, aluminum and plastic

Evolution Horizontal Cable Manager

Velocity Horizontal Cable Manager

Horizontal Cable Managers

Applications:
Network facilities and data center computer rooms

Key Features:
- Open Ring-style or closed, trough-style, single-sided 19″ EIA rack-mount cable managers
- Various styles to match vertical cable managers
- Use above and below patch panels and network switches
- Provides a side-to-side pathway for patch cords
- Closed trough-style managers include removable, hinged snap-on cover(s)

Width (2):
- 19″ EIA

Height (3):
- 1U
- 2U
- 3U

Depth (6):
- 4.9″ (126 mm)
- 5.1″ (130 mm)
- 5.9″ (150 mm)
- 6.2″ (159 mm)
- 6.4″ (163 mm)
- 8.2″ (208 mm)

Construction:
- Riveted aluminum and plastic
- Molded plastic



Evolution® Cable Management

Evolution g1 Single-Sided, Vertical

Part No.	Description	Wt.
35511-703	7'H x 6"W x 13.2"D	57 lb
	2.1 m x 150 mm x 335 mm	25.9 kg
35512-703	7'H x 8"W x 13.2"D	61 lb
	2.1 m x 200 mm x 335 mm	27.7 kg
35513-703	7'H x 10"W x 13.2"D	67 lb
	2.1 m x 250 mm x 335 mm	30.4 kg
35514-703	7'H x 12"W x 13.2"D	73 lb
	2.1 m x 300 mm x 335 mm	33.1 kg
35515-703	7'H x 15"W x 13.2"D	83 lb
	2.1 m x 380 mm x 335 mm	37.6 kg

Evolution g2 Double-Sided, Vertical

Part No.	Description	Wt.
35521-703	7'H x 6"W x 24.5"D	94 lb
	2.1 m x 150 mm x 622 mm	42.6 kg
35522-703	7'H x 8"W x 24.5"D	101 lb
	2.1 m x 200 mm x 622 mm	45.8 kg
35523-703	7'H x 10"W x 24.5"D	110 lb
	2.1 m x 250 mm x 622 mm	49.9 kg
35524-703	7'H x 12"W x 24.5"D	118 lb
	2.1 m x 300 mm x 622 mm	53.5 kg
35525-703	7'H x 15"W x 24.5"D	129 lb
	2.1 m x 380 mm x 622 mm	58.5 kg

Evolution g3 Combination, Vertical

Part No.	Description	Wt.
35571-703	7'H x 6"W x 20.2"D	68 lb
	2.1 m x 150 mm x 513 mm	30.8 kg
35572-703	7'H x 8"W x 20.2"D	72 lb
	2.1 m x 200 mm x 513 mm	32.7 kg
35573-703	7'H x 10"W x 20.2"D	78 lb
	2.1 m x 250 mm x 513 mm	35.4 kg
35574-703	7'H x 12"W x 20.2"D	84 lb
	2.1 m x 300 mm x 513 mm	38.1 kg
35575-703	7'H x 15"W x 20.2"D	94 lb
	2.1 m x 380 mm x 513 mm	42.6 kg

Note: Cable Spools are included with 10"W, 12"W or 15"W (250 mm, 300 mm or 380 mm) Cable Managers. Color is black.



Single-Sided Version Shown

Velocity™ Cable Management

Part No.	Description	Wt.
13901-703	80.5"H x 3.6"W x 9.7"D	18 lb
	2045 mm x 91 mm x 246 mm	8.2 kg
	Single-Sided, Black	
13902-703	80.5"H x 6"W x 9.8"D	20 lb
	2045 mm x 152 mm x 249 mm	9.1 kg
	Single-Sided, Black	
13904-703	80.5"H x 10"W x 10.3"D	32 lb
	2045 mm x 254 mm x 262 mm	14.5 kg
	Single-Sided, Black	
13905-703	80.5"H x 12"W x 10.4"D	34 lb
	2045 mm x 305 mm x 264 mm	15.4 kg
	Single-Sided, Black	
13911-703	80.5"H x 3.6"W x 16.4"D	25 lb
	2045 mm x 91 mm x 417 mm	11.3 kg
	Double-Sided, Black	
13912-703	80.5"H x 6"W x 16.6"D	28 lb
	2045 mm x 152 mm x 422 mm	12.7 kg
	Double-Sided, Black	
13914-703	80.5"H x 10"W x 17.5"D	40 lb
	2045 mm x 254 mm x 445 mm	18.1 kg
	Double-Sided, Black	
13915-703	80.5"H x 12"W x 17.8"D	43 lb
	2045 mm x 305 mm x 446 mm	19.5 kg
	Double-Sided, Black	

Key Accessories

Part No.	Description	Wt.
13935-701	Cable Spool Kit	2 lb
	2" Dia (51 mm) x 6"L (150 mm)	0.9 kg
	Set of 4, Black	
13928-001	Cable Lashing Bar Kit	2 lb
	for 6"W (150 mm) or wider	0.9 kg
	Velocity Cable Managers, Zinc	
13934-717	Cable Ring Kit, 3.6" (91 mm)	3 lb
	wide, for P/N 13901-703, Black	1.4 kg
13934-727	Cable Ring Kit, 6" (152 mm)	11 lb
	wide, for P/N 13902-703, Black	5.0 kg
13934-747	Cable Ring Kit, 10" (254 mm)	14 lb
	wide, for P/N 13904-703, Black	6.4 kg
13934-757	Cable Ring Kit, 12" (305 mm)	16 lb
	wide, for P/N 13905-703, Black	7.3 kg

Note: Use vertical managers on 7'H (2.1 m) racks. Cable Spools are for 6"w (152 mm) or wider vertical managers.



Double-Sided Version Shown

MCS Master Cabling Section

Part No.	Description	Wt.
30091-703	7'H x 4.4"W x 8.08"D	17 lb
	2.1 m x 112 mm x 205.2 mm	7.7 kg
	Single-Sided, Black	
30092-703	7'H x 6"W x 8.08"D	20 lb
	2.1 m x 150 mm x 205.2 mm	9.1 kg
	Single-Sided, Black	
30093-703	7'H x 10"W x 8.08"D	45 lb
	2.1 m x 250 mm x 205.2 mm	20.4 kg
	Single-Sided, Black	
30094-703	7'H x 4.4"W x 16.15"D	40 lb
	2.1 m x 112 mm x 410.2 mm	18.1 kg
	Double-Sided, Black	
30095-703	7'H x 6"W x 16.15"D	45 lb
	2.1 m x 150 mm x 410.2 mm	20.4 kg
	Double-Sided, Black	
30096-703	7'H x 10"W x 16.15"D	53 lb
	2.1 m x 250 mm x 410.2 mm	24 kg
	Double-Sided, Black	

MCS - EFX Extended Fingers

Part No.	Description	Wt.
40092-703	7'H x 6"W x 10.62"D	31 lb
	2.1 m x 150 mm x 269.7 mm	14.1 kg
	Single-Sided, Black	
40093-703	7'H x 10"W x 10.62"D	40 lb
	2.1 m x 250 mm x 269.7 mm	18.1 kg
	Single-Sided, Black	
40094-703	7'H x 12"W x 10.62"D	44 lb
	2.1 m x 300 mm x 269.7 mm	20 kg
	Single-Sided, Black	
40095-703	7'H x 6"W x 21.23"D	56 lb
	2.1 m x 150 mm x 539.2 mm	25.4 kg
	Double-Sided, Black	
40096-703	7'H x 10"W x 21.23"D	69 lb
	2.1 m x 250 mm x 539.2 mm	31.3 kg
	Double-Sided, Black	
40097-703	7'H x 12"W x 21.23"D	75 lb
	2.1 m x 300 mm x 539.2 mm	34 kg
	Double-Sided, Black	

Note: Cable Spools are included with double-sided 10"W or 12"W (250 mm or 300 mm) MCS.



Double-Sided Version Shown

VCS Vertical Cabling Section

Part No.	Description	Wt.
11730-703	7'H x 3.65"W x 6.38"D	14 lb
	2.1 m x 92.7 mm x 162.1 mm	6.4 kg
	Single-Sided, Black	
11374-703	7'H x 6"W x 6.38"D	16 lb
	2.1 m x 150 mm x 162.1 mm	7.3 kg
	Single-Sided, Black	
12096-703	7'H x 3.65"W x 12.75"D	24.0 lb
	2.1 m x 92.7 mm x 323.9 mm	10.9 kg
	Double-Sided, Black	
11729-703	7'H x 6"W x 12.75"D	30 lb
	2.1 m x 150 mm x 323.9 mm	13.6 kg
	Double-Sided, Black	

Contact Tech Support at 800-834-4969 for additional options.

Key Accessories

Part No.	Description	Wt.
12189-001	3.65"W (92.7 mm) Cover	8 lb
	Smoked Acrylic	3.6 kg
12188-001	6"W (150 mm) Cover	9 lb
	Smoked Acrylic	4.1 kg
12370-001	Finger Snaps	1 lb
	Set of 2, Black	0.5 kg
12370-002	Finger Snaps	2 lb
	Set of 12, Black	0.9 kg



CCS Combination Cabling Section

Part No.	Description	Wt.
30161-703	7'H x 3.65"W x 12.24"D	29 lb
	2.1 m x 92.7 mm x 310.9 mm	13.2 kg
	Double-Sided, Black	
30162-703	7'H x 6"W x 12.24"D	34 lb
	2.1 m x 150 mm x 310.9 mm	15.4 kg
	Double-Sided, Black	
30163-703	7'H x 10"W x 12.24"D	46 lb
	2.1 m x 250 mm x 310.9 mm	20.9 kg
	Double-Sided, Black	
30164-703*	7'H x 3.65"W x 14.61"D	33 lb
	2.1 m x 92.7 mm x 371.1 mm	15 kg
	Double-Sided, Black	
30165-703*	7'H x 6"W x 14.61"D	38 lb
	2.1 m x 150 mm x 371.1 mm	17.2 kg
	Double-Sided, Black	
30166-703*	7'H x 10"W x 14.61"D	49 lb
	2.1 m x 250 mm x 371.1 mm	22.2 kg
	Double-Sided, Black	

**Note: Use with 6"D (150 mm) Standard Rack*

CCS-EFX Extended Fingers

Part No.	Description	Wt.
40098-703	7'H x 6"W x 14.94"D	38 lb
	2.1 m x 150 mm x 379.5 mm	17.2 kg
	Double-Sided, Black	
40099-703	7'H x 10"W x 14.94"D	52 lb
	2.1 m x 250 mm x 379.5 mm	23.6 kg
	Double-Sided, Black	
40100-703	7'H x 12"W x 14.94D	56 lb
	2.1 m x 300 mm x 379.5 mm	25.4 kg
	Double-Sided, Black	

Key Accessories

Part No.	Description	Wt.
15008-001	Cable Spools	2 lb
	2.5"Dia (64 mm)	0.9 kg
	Set of 4, Black*	
12370-001	Finger Snaps	1 lb
	Set of 2, Black	0.5 kg
12370-002	Finger Snaps	2 lb
	Set of 12, Black	0.9 kg

**Note: Cable Spools are for 10"W or 12" W (250 mm or 300 mm) CCS or CCS-EFX.*



Horizontal Cable Managers

Evolution® Horizontal Cable Manager

Part No.	Description	Wt.
35441-701	1U x 19"EIA x 8.2"D	4 lb
	(208 mm), Black	1.8 kg
35441-702	2U x 19"EIA x 8.2"D	5 lb
	(208 mm), Black	2.3 kg
35441-703	3U x 19"EIA x 8.2"D	6 lb
	(208 mm), Black	2.7 kg

Velocity Horizontal Cable Manager

Part No.	Description	Wt.
13930-701	1U x 19"EIA x 5.9"D	2 lb
	(150 mm), Black	0.9 kg
13930-702	2U x 19"EIA x 5.9"D	3 lb
	(150 mm), Black	1.4 kg
13930-703	3U x 19"EIA x 5.9"D	3 lb
	(150 mm), Black	1.4 kg

Universal Horizontal Cable Manager

Part No.	Description	Wt.
30139-719	1U x 19"EIA x 4.9"D	2 lb
	(126 mm), Black	0.9 kg
30130-719	2U x 19"EIA x 5.1"D	3 lb
	(130 mm), Black	1.4 kg
30131-719	3U x 19"EIA x 5.1"D	4 lb
	(130 mm), Black	1.8 kg
30339-719*	1U x 19"EIA x 6.2"D	3 lb
	(159 mm), Black	1.4 kg
30330-719*	2U x 19"EIA x 6.4"D	4 lb
	(163 mm), Black	1.8 kg
30331-719*	3U x 19"EIA x 6.4"D	5 lb
	(163 mm), Black	2.3 kg

*Note: *Use deep panel models when MCS is center-mounted on Standard or Universal Rack. Other sizes and styles are available.*

19" Horizontal Wire Management Panel

Part No.	Description	Wt.
13070-719	1U x 19"EIA x 4"D	2 lb
	(100 mm), Black	0.9 kg
13075-719	2U x 19"EIA x 4"D	2 lb
	(100 mm), Black	0.9 kg

Contact CPI Technical Support at 800-834-4969 or techsupport@chatsworth.com for assistance.

See CPI cable fill table at www.chatsworth.com/cablefill for all cable managers.

CPI's online Product Configurator is an easy-to-use confidential tool that guides you through the steps and selections necessary to create customized Systems. Check out the Product Configurator at www.chatsworth.com/configurator.

CHATSWORTH PRODUCTS, INC.

www.chatsworth.com • techsupport@chatsworth.com • +1-800-834-4969

©2011 Chatsworth Products, Inc. All rights reserved. CPI, CPI Passive Cooling, MegaFrame, Saf-T-Grip, Seismic Frame, SlimFrame, TeraFrame, Cube-iT Plus, Evolution, OnTrac, and QuadraRack are federally registered trademarks of Chatsworth Products, Inc. GlobalFrame, Simply Efficient and Velocity are trademarks of Chatsworth Products, Inc. All other trademarks belong to their respective companies. Rev.8 1/11 MKT#60020-206